

# 10.1 Inch FHD Portable LCD Monitor



With the PRM1014, Full HD portable monitor, OSEE has delivered a single model that meets virtually all needs for field production. We started by using 10-bit signal processing technology and 1920×1200 IPS screen that is viewable from any angle. Then added a full set of features that provide all the benefits of our The monitor itself is also very power efficient that it can operate for over 9 hours with an F970 battery and even longer with available adapters for V-Mount or Anton Bauer batteries.

### Highlights


### 9-hour Battery Life

The PRM-1014 can operate for over 9 hours with an F970 battery and even longer with available adapters for V-Mount or Anton Bauer batteries.



### IPS 178° Wide Viewing Angle Full HD Display Screen

With IPS LCD panel and 178° wide viewing angle, PRM1014 shows excellent color from every angle.



### Lightweight and Portable Body

The portable PRM1014 features unsurpassed damge resistance glass and durable and lightweight magnesium metal shell. 4-20 mounting is provided on all sides and a flip stand makes this the perfect option for stand-alone talent monitoring in the stadium announce booth.

### **Shooting Assist**

Our Focus Assist is another adaptation from larger models. Unlike some monitors that simply zoom to a picture location, the PRM1014 focus assist covers the entire depth of field. A Luma Zone function easily displays over exposure issues providing confidence to the DP in their scene composition.





Luma Zone

### Analytics

Waveform and Vector scope displays are provided with a number of adjustable features in addition to multiple channel audio monitoring for analog and digital sources.





Vector

Waveform





Front View

Side View

# 10.1 Inch FHD Portable LCD Monitor



## **Specifications**

Model	PRM1014
Size	10.1"
Resolution	1920×1200
Dot Pitch	0.113×0.113
Color Depth	16.7M
ViewingAngle(deg)	178° ×178°
Brightness(cd/m²)	400
Contrast	800
Input Terminals	
Video (Composite)	BNC (×1), 1Vp-p+/-3dB sync negative
SDI	BNC(×2), 800mVp-p +/-10%
HDMI	HDMI Type-A, compatible with DVI-D
Audio	2ch Analog stereo, 5dBu, Impedance ≥ 47K, RCA Connector
Output Terminals	
Composite	BNC(×1), active loop through, automatic termination
SDI	BNC(×2), 800mVp-p +/-10%, active loop through
Audio Monitor	1ch Analog stereo, 5dBu, Impedance ≤ 500Ω, RCA Connector
Earphone	3.5mm connector
Speaker	4Ω, 2W×2
<b>External Control</b>	
GPI	4GPI Input, RJ45 Connector
RS485	RS485, can be cascaded, RJ45 Connector
Ethernet	10/100M adaptive, RJ45 Connector
General	
Power Supply	DC12V/XLR
Power Consumption	10Wmax
Operating	0°C to 35°C (32° F to 95° F)
Temperature	Recommended: 20° C to 30° C (68° F to 86° F)
Operating Humidity	20% to 80% (No condensation)
Weight (without battery)	1.5Kg ( 3.3lbs )
Accessories	
Standard Accessories	Optical Glass; AC Power Cable; AC-DC Adapter
Optional Accessories	1) Battery Plate: V-Mount Battery Bracket; Anton Battery Plate; SONY F-970 Battery Plate; Panasonic D54S Battery Plate; Canon Battery Plate 2) Hotshoe Adapter 3) Articulating Arm 4) Sun Hood

<sup>\*</sup>Specifications are subject to change without notice.

# Highlights


### Multiple Format Signal Inputs


In order to meet different signal monitoring requirements, PRM1014 accepts multiple format signal inputs including 3G/HD/SD-SDI and HDMI. The format is easily identifiable with an adjustable on screen display.






### **Dimensions**







Main Body: 254×176×34 (mm) 10×6.9×1.3 (inch)

### **OSEE TECHNOLOGY CO., LTD.**

Add: No.22 Building, No.68 Zone, Beiqing Road, Haidian District, Beijing 100094 China Tel: +8610 6243 4168-8017 Fax: +8610 6243 4169

E-mail: sales@osee-dig.com

#### OSEE AMERICAS LTD.

Add: 43218 Christy St Fremont, CA 94538

Tel:+1 510 996 4499

E-mail: info@oseeamericas.com Toll Free: 866 625 6106 Online Mall: www.oseedirect.com