

## VZ-156LED-HDR

## 15.6" 3G-SDI/HDMI HDR PROFESSIONAL MONITOR



MODEL#		VZ-156LED-HDR
	DIS	PLAY
Screen Size		15.6"
Max. Resolution		1920 x 1080 (Full HD) IPS pixel
Pixel Pitch		0.17925 mm x 0.17925 mm
Brightness		1000 cd/m²(Typical)
Contrast Ratio		1000:1
Aspect Ratio		16:9
Viewing Angle (H/V)		178° / 178°
Color Space		101% Rec. 709
HDR		ST2084 300/1000/10000/HLG
	INTE	RFACE
3G-SDI In / Out		1 / 1 (Loopthrough)
HDMI 1.4b In		1
VGA		1
AV		1
	Input	Format
SD-SDI/HD-SDI/3G-SDI (Level A&B)		1080p (24/25/30/50/60p), 1080i (50/60p),
		720p(50/60p)
НОМІ		2160p (24/25/30p), 1080p (24/25/30/50/60p),
		1080i (50/60p), 720p(50/60p)
	All	DIO
Built in speaker		1W x 2
SDI		16ch 48kHz 24 bit
HDMI		8ch 24 bit
Ear Jack		3.5 mm - 2ch 48kHz 24 bit
Zur such	DIMENSION	IS & WEIGHT
Outline Dimension (W x H x D) (inch)		15.31 x 10.23 x 1.48"
Outilité Billi	(W x H x D) (mm)	389 x 260 x 37.6 mm
Net Weight	( <b>VV</b> X 11 X D) (111111)	6.32 lbs (2.87 kg)
Wet Weight	GEN	ERAL
Power	Electrical Ratings	DC 12~24V
Tower	Consumption	≤24 W (15V)
Warranty	Consumption	2 Years
Operating Temperature		-22 ~ 158°F / -30 ~ 70°C
		·
Humidity at High Operating Temperature		90% RH for 240 hrs, TA=+ 140°F (60°C)
Storage Temperature		-4~140°F/-20~60°C
Battery Plate		V-mount / Anton Bauer mount (Option)
Package Include		12V DC Adapter x 1, Manual x 1, VGA Cables
		HDMI A/A Cable x1, AV Cable x1,
		Rack Mount Bracket Set x1,
		Desktop Stand Set x 1



When HDR is activated, the display reproduces a greater dynamic range of luminosity, allowing lighter and darker details to be displayed more clearly. Effectively enhancing the overall picture quality.



Featuring an amazing 1000 cd/m<sup>2</sup> high bright LCD screen, with sunshine readable screen which cover 101% Rec. 709 color space, therefore the gear suitable for any innovative outdoor framing.



Multiple Video Interface (3G-SDI, HDMI, VGA and Analog Video) provided.



With Audio Level Meter turned on, it is used to monitor current audio output and avoid being indifferent after an audio interruption as well as keep the sound within a reasonable DB range.



It can be installed and fixed on the wall or the 19-inch Rack (6U) through the VESA 75x75 mm screw points at its back. Optional Wall Mount Adaptors or 19-inch Rack Adaptor (VZ-RMK08) is available

## **Contact ViewZ**

• Address: 177 W. Orangethorpe Ave., Placentia, CA 92870

• Phone: (714) 996-1177, Fax: (714) 996-1138

• Sales: sales@viewzusa.com