
8 / 16 Port 18.5" DVI LCD KVM Console (LD1808 / LD1816)




Kinan Overview

The DVI KVM console integrates an 18.5" widescreen LCD monitor, keyboard & touchpad, and an 8/16 ports DVI KVM switch in a 1U rack housing. It can control 8/16 computers with one monitor, keyboard and mouse. Connect computers via standard DVI port, resolution is up to 1920 x 1080@60Hz. It is easy and fast to install the KVM console, you just need to connect corresponding cables to the right ports of KVM and its module without software configuration.



| 1 | LCD Monitor | 6 Touchpad | |
|---|----------------------|---------------------------|--|
| 2 | Rear Bracket Slot | 7 Handle | |
| 3 | Display Menu Buttons | 8 Release Switch | |
| 4 | Mounting Bracket | 9 Display Panel | |
| 5 | Keyboard | 10 Port Selection Buttons | |

Structure




| | ● | + @ @ | e | 100-240Vac 60-60Hz |
|-------|---|---------------|--|--------------------|
| 1 2 3 | | 4 | | 5 |
| | PC 15 PC 15 PC 15 PC 14 PC 14 PC 13 PC 13 PC 14 PC 13 PC 13 PC 15 PC 13 PC 15 | PC 12 PC 11 | PC 10 PC 10 PC 2 PC 2 PC 1 | 100-240Vac 50-60Hz |

| 1 | Ground Connection Screw | 4 | PC Port |
|---|-------------------------|---|-----------------|
| 2 | Console Port | 5 | Power input(AC) |
| 3 | USB Port | | |

Features

- 18.5" Full HD LCD monitor, high brightness, high resolution;
- 1U height, suitable height for standard 19"rack mount, metal structure;
- Ultra slim 99 keys keyboard with small numeric keyboard;
- Superior video quality 1080P(1920×1080@60Hz)
- A single USB console controls up to 8 or 16 computers
- Auto PS/2 and USB interface detection
- Supports wireless keyboard and mouse from different suppliers
- Two level password security only authorized users view and control computers; up to four users and an administrator with a separate profile for each
- Broadcast mode operations simultaneously performed on all selected computers
- Multiplatform support Windows, Linux, Mac and Sun
- Supports multimedia USB keyboard(PC, Mac and Sun)
- USB or PS/2 keyboard emulation computer boot even the console focus is else where
- Convenient computer switching via front panel pushbuttons, hotkeys, OSD
- Auto scan feature for monitoring user-selected computers
- Hot pluggable add or remove computers without having to power down the switch
- Quickly select your computer by naming the server or inputting SN number of the server

Connection Diagram





Specifications

| Model | | LD1808 | LD1816 | | | |
|--------------------------------|--------------------|---|--------|--|--|--|
| Computer connect | ctions | 8 | 16 | | | |
| Port emulation Keyboard, mouse | | PS/2, USB | | | | |
| | LCD Model | FHD TFT | | | | |
| | View Area | 18.47″ | | | | |
| | Optimum Resolution | 1920×1080@60Hz | | | | |
| LCD Monitor | Display Color | 16.7 M | | | | |
| | Brightness | 500cd/m² (T y p) | | | | |
| | Contrast Ratio | 1000:1 (Typ) | | | | |
| | Pixel Pitch(mm) | 0.213(H) × 0.213(W) | | | | |
| | X/Y Resolution | >1000 points /inch,(40 points/mm) | | | | |
| Mouse | Scroll Wheel | Supports scroll wheel function | | | | |
| Keyboard | | 99 keys (82 keys main keyboard +17 independent small numeric keyboard) | | | | |
| Port Selection | | Pushbuttons, hotkeys, OSD menu | | | | |
| Input Power | | 100V – 240Vac, 50 ~ 60Hz, <1.5A | | | | |
| DVI Signal | | DVI-D | | | | |
| Power Consumpt | ion | 35W | 38W | | | |
| Operating Tempe | rature | 0 − 40 °C | | | | |
| Store Temperatur | е | -20 − 60 °C | | | | |
| Humidity | | 0 – 80% RH, non-condensing | | | | |
| Net Weight | | 11.5kg | 11.7kg | | | |
| Product Dimensio | on (W × D × H) | 448mm×560mm×42.5mm | | | | |
| Package Dimensi | on (W × D × H) | 765mm×615mm×185mm | | | | |
| - | | | | | | |