7" Android system CCTV Tester with WIFI, Browser, POE, cable test etc

Model: IPC-8600 Plus series

- 7 inch retina touch screen, 1920*1200 resolution
- 8MP CVI/ TVI/ AHD, 8MP EX-SDI, HD-SDI, 3G-SDI*
- H.265/H.264, 4K video display via mainstream
- Dahua, Hikvision, Axis etc ONVIF camera test
- Chrome browser, set Axis etc cameras parameters
- Built in WIFI, create WIFI hotspot
- HDMI input & 4K output
- DC12V 2A, DC48V PoE power output
- RJ45 cable TDR test, cable quality test
- Cable tracer and video level meter



Features

Camera test:

- 7 inch retina touch screen, 1920*1200 resolutions
- H.265 & H .264 IP, 4K video display via mainstream
- 8MP TVI test,3840 x 2160P 12.5/15 FPS,4xzoom ,video record &playback ,coaxial PTZ control & call OSD menu *
- 8MP AHD test, 3840x2160P 15 FPS, 4xzoom, video record & playback, coaxial PTZ & call OSD menu *
- 8MP CVI test, 3840 x 2160P 12.5/15FPS, 4xzoom, video record& playback, coaxial PTZ & call OSD menu *
- 8MP EX-SDI test, 3840 x 2160P 25/30FPS,4xzoom, video record& playback, coaxial PTZ & call OSD menu *
- HD-SDI test, 1920 x 1080P 25/30/50/60 FPS, 4xzoom, video record& playback, coaxial PTZ & call OSD menu *
- 3G-SDI test, 1920 x 1080P 50/60 FPS, 4xzoom, video record& playback, coaxial PTZ & call OSD menu *
- Rapid ONVIF, Auto log in and display image, create testing report
- AXIS, Hikvision camera test, enter ONVIF app, input username and password to test
- CVBS camera test and PTZ control
- IPC TEST (Non-ONVIF test), HIK test tool (Hikvision camera), DH test tool (Dahua camera)
- Video level meter, peak video signal level, SYNC signal level, Color bar chroma level measurement
- DC12V/2A power output, camera can be powered from DC 12Votage
- 48V PoE power output power
- Rapid video, just by one key to detect all network cameras and auto display
- Built in Wi-Fi, display image from the wireless camera, create WIFI hotspot
- CVBS loop test, the tester send and receive color bar generator signal, to check BNC cable
- Enhanced Color bar generator, PAL/NTSC multi-system color bar video generator

Cable test:

• Improvement cable tester, UTP cable, telephone cable etc order and connectivity test, can save testing report, if special number, need customized

- RJ45 cable TDR test, test cable pair status, length, attenuation, reflectivity, impedance, skew etc
- Cable tracer, search BNC cable, network cable and telephone cable from the mess cables
- TDR cable test: BNC cable, network cable, telephone cable, RVV cable and elevator cable, cat 5/6 cable
- 's length and short circuit. measurement range 1.2KM*

Other functions:

- Network tool: Ping, IP scan, Port Flash, DHCP server, Trace Route
- POE & power information, DC12V& PoE power and voltage output /input measurement
- Tester Play: Tester, android version mobile phone and PC display at the same time
- Shortcut button, drop-down menu, can select Poe power, IP setting, CVBS, LAN info, HDMI IN etc
- HDM input,720×480p /720×576p /1280×720p /1920×1080p /1024×768p/1280×1024p /1280×900p /1440×900p display, record and snapshot

• Traffic monitoring, display network port or WIFI connection real-time upload and download speeds and other network parameters

- Self -update software, you can install apps with android version
- Media player, 4K video files and MKV/MP4 media files play
- Quick office, quick office app (support excel, word, ppt format) doc. editable
- 8GB SD card including
- Display its genuine resolution of the IP camera images
- Audio in, support record and save the audio/LED lamp, calculators, music players and other application tools
- 7.4 V /7000mAh Lithium Ion Polymer Battery, after 7~8 hours charging , working time lasts 16 hours

	Item series	IPC-	8600 Plus series
LCD	Display	New 7 inch IPS touch	
		screen, 1920*1200 resolution	
Video Mode	CVBS	1 channel BNC input &	1 channel BNC
		looped output,NTSC/PAL (Auto adapt)	
		Analog video level meter, peak video	
		signal level,SYNC signal level, Color bar	
		chroma level measurement	
		PTZ control, RS485 control, Baud 600-	
		115200bps,compatible with more than	
		30 protocols such as PELCO-D/P,	
		Samsung, Panasonic etc	
		CVBS loop test	the tester
			send and
			receive color
			bar generator

Specifications

			signal ,check	
			BNC cable	
		IP Discovery/Quick ON\		
		/RTSP play/Client APK		
			Auto view the	
		Rapid Video	video, create	
		Rapid Video	testing report	
			Activate	
			hikvision	
			camera,	
	IP camera test	Hik test tool	modify the	
	4k/H.265/H.264		user name,	
			password and	
			IP parameters	
			Dahua camera	
			test, modify	
		Dahua test tool	the user name,	
			password and	
			IP parameters	
		IP& CVBS test at the sar		
	IP& CVBS test	,converter test from analog to digital		
		with dual test window		
		8MP TVI camera test, 3840 x 2160P 15		
		FPS, UTC control/ call OSD menu *		
		8MP CVI camera test, 3840 x 2160P		
		12.5/15 FPS,UTC control call OSD menu		
	Coaxial HD test*	*		
		8MP AHD test, 3840 x 2160P 15FPS,		
		UTC control & call OSD menu*		
		8MP EX-SDI, HD-SDI, 3G-SDI, UTC		
		control & call OSD menu*		
	HDMI input	1 channel HDMI input, support 1080P		
	Zoom Image	4x zoom, to enlarge image, Screen		
		snapshot,record ,save ,view and record		
	_	and play back		
Amelandel	Color bar generator	Output one channel PAL/NTSC color		
Analog Video out		bar video signal for testing monitor or		
		video cable		
Device extend	DoE nower output	48V PoE power output, max power		
	PoE power output	25.5W		
Power output	DC12V power	DC12V /2A power output		
California		BNC cable, network cable, telephone		
Cable test	TDR cable test *	BINC Cable, network cab	le, telephone	

		5/6 cable's length and short circuit.	
		measurement range 1.2KM *	
	Cable tracer	Search BNC cable, network cable and	
		telephone cable from the mess cables	
		Test UTP cable connection status and	
	UTP cable test	display on the screen. Read the number	
		on the screen	
		Test cable pair status,	
	RJ45 cable TDR test	length,attenuation, reflectivity,	
		impedance, skew etc.measurement	
		range 180M.	
TesterDlay	Screen projection: tester, mobile phone and PC display at the same time		
TesterPlay	(For android version mobile phone)		
Network test	Trace route, Link monitor,DHCP server, port flashing,Ping test		
Wi-Fi	Built in WIFI,speeds150M,display wireless camera image		
	1 channel audio signal input, test whether sound normal,1 channel		
Audio test	audio signal, to connect headphone		
	Captures and analyzes the command data from controlling		
Data monitor	device, also can send hexadecimal		
	Measurement POE switch or PSE power supply voltage and cable		
PoE test	connection status		
Drop-	You can select PoE power switch ,IP setting,CVBS, LAN info, HDMI IN		
down menu	functions etc in any interface		
External powe			
r supply	DC12V 2A		
Battery	Built-in 7.4V Lithium polymer battery, 7000mAh		
Rechargeable	After charging 7~8 hours, normal working time 16 hours		
Operation set	OSD menu,select your desired	C C	
ting	-	n, Polish, Spanish, Japanese etc	
Auto off			
Working Tem	1-30 (mins)		
5	-10°℃+50°℃		
perature Working Hum			
Working Hum	30%-90%		
idity			
Dimension/Wei	231mm x 172mm x 52mm ,	/ 1.26Kg	
ght		-	
	nizable functions, if need cus s IPC-8600MOVTADHS Plus	tomize them, QTY MOQ is 50pcs,Full	
М	Digital Multimeter :DC and AC voltage measurement, Resistance		
	measurement, Continuity test, Diode measurements, Capacitance		
	measurement		
0	Optical power meter, Wavelength:		
	1625,1550nm,1490nm,1310nm,1300nm,850nm, measurement range ,-		
	, , , ,	. , ,	

	70 \sim +10 dBm, for optical power testing and Fiber link loss relative	
	measurement	
V	Visual fault locator :10mW visual fault locator with 650nm wavelength	
	can emit red laser sources to test multi-mode and single mode fiber's	
	bending and breakage, test range 10KM	
т	TDR cable test: BNC cable, network cable, telephone cable, RVV cable	
	and elevator cable, cat 5/6 cable' s length and short circuit.	
	measurement range 1.2KM	
А	AHD camera test: 8MP AHD test,3840 x 2160P 15FPS, UTC control &	
	call OSD menu	
н	TVI camera test: 8MP TVI camera test,3840 x 2160P 15 FPS, UTC	
	control & call OSD menu	
D	CVI camera test: 8MP CVI camera test,3840 x 2160P 12.5/15 FPS,UTC	
	control & call OSD menu	
S	HD-SDI/EX-SDI/3G-SDI camera test ,UTC control & call OSD menu	
L	Video level meter :PEAK ,SYNC signal level,color burst chroma level	
	measurement	
С	Cable tracer :search BNC cable, network cable and telephone cable	
	from the mess cable	
	1	