

WAT-06U2D 1/2.8" USB2.0 Full HD Wearable Color Camera

Upgraded the performance from WAT-02U2D


NEW



Key features

- Resolution 1.3 times higher and sensitivity 3.5 times higher than the previous model
- USB Video Class & USB Bus Power (plug & play)
- Full HD (Max. frame rate 30fps)
- Enable the live video transmission via the smartphone or tablet by its Wi-Fi or 4G/3G
- Water resistant built for outdoor use (IPX7 compliance)

Dimensions




Specifications

| | | |
|-----------------------------------|--|--|
| Pick-up element | 1/2.8 inch CMOS image sensor | |
| Number of effective pixels | 1945(H) × 1097(V) | |
| Unit cell size | 2.9µm(H) × 2.9µm(V) | |
| Imaging system | RGB primary color bayer arrangement mosaic filters on chip | |
| Synchronizing system | Internal | |
| Scanning system | Progressive | |
| Output size | 1920x1080, 1280x720, 640x480, 320x240 | |
| Max. frame rate | 30 fps | |
| Video compression | MJPEG, YUY2 | |
| Video output | USB Video Class (Compatible) | |
| Resolution (H) | More than 900TVL (Center) | |
| Minimum illumination | 0.3 lx F2.0 (AGC ON=36dB, Shutter=OFF) | |
| | 0.07 lx F2.0 (AGC ON=36dB, Shutter=1/7.5 sec.) | |
| S/N | - | |
| Function settings | Camera Viewer | |
| AE mode | Fixed | 1/15, 1/7.5, 1/4 sec. |
| | | 1/30, 1/60, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000 sec. |
| | EI | 1/30 - 1/8000 sec. 1/7.5 - 1/8000 sec. |
| White balance | ATW, MWB | |
| AGC | ON | 0 - 36dB |
| | OFF | - |
| MGC | 0 - 72dB (1dB step) | |
| Gamma characteristics | γ≠USER (Level adjustable) | |
| Noise reduction | - | |
| Wide dynamic range | - | |
| Lens iris | - | |
| Back light compensation | BLC | |
| White blemish correction | - | |
| Sharpness | Level adjustable | |
| Defog | - | |
| Digital zoom | ×1, ×1.38, ×2.25 *1 | ×1, ×1.2, ×1.5 *2 |
| Privacy mask | - | |
| Mirror image | - | |
| Freeze | - | |
| Motion detection | - | |
| Neg.image | - | |
| Interface | USB (High speed) | |
| Power supply | USB +5V | |
| Power consumption | 0.65W (130mA) | |
| Operating temperature | -10 - +50°C | |
| Storage temperature | -30 - +70°C | |
| Operating / Storage humidity | 95% RH or less (Without condensation) | |
| Standard lens | M3620BC-12 (F3.6 F2.0) | |
| Cable length | 1.2m (Max.3.0m) | |
| Weight | Approx. 85g | |
| Accessories | - | |
| Recommended System Specifications | CPU | Intel® Core TM i Series |
| | RAM | 2GB or larger |
| | Others | USB2.0 Port, 1920×1080 or better resolution display |
| Operation Confirmed OS | Windows 10 32bit/64bit, Android 4,0 or newer | |

*1: Output format: 640x480 *2: Output format: 1280x720

Options



*WAT-06U2D with optional lenses are made to order.

* Supporting various transmission system (Please contact us for the details)