



HDMI Distributor, OHD14/ OHD18

Description

OPTICIS HDMI Distributor, OHD 14 or OHD18 makes one(1) HDMI video source split into four(4) or eight(8) displays, simultaneously without any signal loss or digital; noise. It guarantees to support full channels. HDMI 1.3/HDCP1.1 compliant.

Technical Features

Model Name	OHD14	OHD18
Resolution	VGA to WUXGA , 480p to 1080i/p	
Input TMDS Signal	1.2V	
Input DDC Signal	5V	
Power Supply	DC +5V , 2.6A	DC +5V ,6.0A
Dimension(mm)	200 x 104 x 25	436 x 120 x 44
Weight(kg)	0.28	0.68
Operating Temp.	0°C~40°C	
Storage Temp.	-20 ℃~60 ℃	
Operating Humidity	30%~80%	
Storage Humidity	60%	
Power Consumption	5.5W	18W

Specification

- Offers many types of option for EDID (OHD14)
- Supports DDC/HDCP
- CEC function
- Supports up to WUXGA (1920x1200), at 60Hz and HD 1080i/p (1920x1080).
- Provides status LED indicators.
- Compatible with HDMI-DVI cable.



Opticis Co., Ltd. 3F, 305, Sanseong-daero Sujeong-gu Seongnam-si, Gyeonggi-do, 13354 South Korea Tel: +82 (31) 719-8033 Fax: +82 (31) 719-8032 tosales@opticis.com



All contents are subject to be changed without prior notice.