#### **Product Specifications**

- Sony super-low-light 8M pixel sensor, clear and natural imaging in low-light conditions, providing ultra FHD image quality.
   Resolution: (16.9) 1920 x 1080, 1280 x720 at 60, 30, 15fps; 1600 x
- 900,960 x 540, 848 x 480, 800 x 448, 640 x 360, 424 x 240, 320 x 180 at 30,15fps; (4:3) 1280 x 960, 800 x 600, 640 x 480, 480 x 360, 320 x 240 at 30 15fns
- SmartFrame for automatic FOV adjustment to fit all participants. · Smart Composition function offers great visibility for the individual
- participant in the meeting room. · Innovative Preset Framing: Follow the presenter based on preset
- · WDR: Superb backlight compensation technology for optimizing light balance in high-contrast conditions.
- Zoom: 36X\* total zoom (12X optical zoom)
  Field of view(D/H/V): 80.5°/72.8°/44.1°
- · Lens focal length: 3.9 mm (wide) ~ 46.8 mm (tele)
- · Lens F#: 1.6 (wide) ~ 2.8 (tele)
- · Mirror, flip, white balance: Auto/manual override via PTZApp 2
- · Minimum focus distance: 1m
- Standard tripod screw holes and Kensington slot.
- · People-counting API: Enterprises and third-party software providers can obtain people-counting data for a better understanding of meeting space usage.

#### Speakerphone

- · Advanced noise suppression
- · Dual-omnidirectional microphone
- · 3.5 mm phone-in jack
- · 35 mm line out
- · Speaker. 6W, Adjustable to 90dB SPL at 0.5 m
- · Touch controls for volume down/up, mute, phone input (Microsoft Teams SKU w/o this function), call, hang-up,
- · Bridge phone-in and USB into one call
- Security: Kensington slot

#### Control

- · IR remote control
- (128 preset points via VISCA command) · Remote side: VISCA over IP, IP (RJ45)
- UVC/UAC plug-and-play
   WebUI: Browser IP access via Chrome
- (does not support Internet Explorer)
- · PTZApp 2

#### Video Format

- Network video compression format: H.264
   Network protocol: RTSP, RTMP

#### **Motorized Pan & Tilt Movement**

- · Pan: ±170°
- Tilt: +90° (up) -30° (down)
- Fast and quiet pan / tilt movement

#### Connectivity

- 12V/5A power adaptorMini DIN9 for RS232 in & out connection (VISCA control panel and camera daisy-chain)

- · 3.1 Gen 1 Type-B, backward compatible with USB 2.0

## Mount

- · Camera wall-mount bracket included
- Optional foldable TV mount
- · Optional ceiling mount

#### **System Requirements**

- · Google Chromebox 3 version 94.0.4606.114 or later

#### **PC Hardware Requirement**

- 3.2 GHz Intel® Core™ i5-4460 processor
- · 4 GB RAM or more
- · USB 3.1 port, backward compatible with USB2.0 port

#### **Environmental Data**

- Operation temperature: 0°C ~ 40°C
- Operation humidity: 20% ~ 80%
- · Storage temperature: -20°C ~ 60°C • Storage humidity: 20% ~ 80%

- Package dimensions: 259 x 259 x 349 mm
- Package weight: 5.805 kg
- · Camera: 150 x 153 x 182 mm/1.53 kg
- · Speakerphone: 220 x 181.5 x 49.5 mm/0.85 kg

#### **Optional Accessories**

- Expansion Speakerphone
- Expansion Microphone
- · Foldable TV mount
- USB3 1 fiber extender 10m

## Web page browser requirement

- Chrome: version 76.x or above
- Firefox: version 69 or above · IE: Not support

#### **Power Supply**

- $\cdot$  AC 100V  $\sim$  240V, 50/60 Hz
- · Consumption: 12V, 5A

#### **Free Applications for Meeting Collaboration** (Windows® and Mac)

### EZManager 2: Camera Central Management Software

Remotely manage group FW/SW updates, camera control, and settings.

### PTZApp 2: Camera Settings Software

- Upgrade firmware automatically or manually
- Control camera
- Set parameters and adjust camera image
- Diagnose operating status
- Real-time streaming/ annotating/ image capturing/ video recording

#### **Package Contents**

- · VC520 Pro3 Camera
- Remote control
- · Power adapter
- · Power cord (6 ft/1.8 m)
- USB2.0 type-B to type-A cable (16.5 ft/5 m)
- Camera to Speakerphone Cable (33ft/ 10m)
- 3.5 mm aux cable (3 ft/0.9 m)
- QR code card

Warranty

- Wall-mount bracket
- · ¼" Tripod screw
- · 2 Expansion microphones and 5 m Cable\*
- Camera / Speakerphone: 3 years\*
- Accessories: 1 year

#### **Compatible Applications**

Zoom, Microsoft® Teams, Skype for Business, Skype, Google Meet, Intel® Unite™, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting® , TrueConf, Adobe® Connect™, Cisco Webex® , Fuze, GoToMeeting™,

#### **Audio Format**

- · Network protocol: RTSP, RTMP

# **Hardware Specifications**



LAN for IP streaming

DC 12V Power Jack Speakerphone Port (Blue cable) HDMI Output Port (to TV) USB3.1 Type-B Port RS-232 In/Out Port

©2023 AVer Information Inc. All rights reserved.

\* Specifications may vary depending on location and are subject to change without notice

**SPEAKERPHONE** BACK PANEL

speakerphone and



## **SPEAKERPHONE**





www.aver.com

All brand names and logos are trademarks of their respective companies.

(€ F© RoHS 202310



Standard edition



AVer VC520 Pro3

Professional camera and speakerphone for mid-to-large room meeting

# The VC520 Pro3 stands out as an advanced conferencing system. It boasts a 36X total zoom PTZ camera, enhanced AVer SmartFrame, Preset Framing, and a Sony WDR sensor. Additionally, the VC520 Pro3 offers 3-way outputs, including HDMI connectivity, for a wider range of streaming options and a superior video and audio experience. But what truly sets the VC520 Pro3 apart is its Smart Composition feature, an embedded AI function designed to swiftly capture high-quality closeup images of meeting participants. And with an extended speakerphone solution, the VC520 Pro3 delivers an exceptional video conferencing experience.







Smart Composition





Speakerphone

# Dominate the Details with 36X\* **Total Zoom Lens and WDR**

Host flawless meetings with the VC520 Pro3's PTZ lens that offers, boasting an expansive 80.5° diagonal field of view for capturing wide shots and offering versatile pan and tilt controls for focusing on presenters, attendees, whiteboard content, or physical objects. Harness precision with a 12X optical lens and a remarkable 36X\* total zoom, including a 24X lossless zoom for exceptional clarity in remote communication. Plus, the Sony WDR sensor ensures adapt to diverse lighting conditions, making the VC520 Pro3 the perfect conferencing camera for mid-to-large rooms.

\*Use PTZApp 2 to set up 36X zoom



# **Accurate Attendee Capture with AVer Smart Composition – No Installation Required**

The VC520 Pro3 is one of the first PTZ camera and audio systems on the market to offer a Smart Composition feature — technology usually only found in enterprise-grade devices. Smart Composition uses Al algorithms to automatically frame each participant's face or body perfectly. It's a click-to-play feature with no software setup needed. Seamlessly transition between headshots and half-body views, effortlessly switching from individual to group images. With the VC520 Pro3, you'll enjoy high-definition views of participants and easy meeting setups for optimal productivity.



The VC520 Pro3 facilitates simultaneous 1080p/60fps presentations through HDMI and USB 3.1 streaming or RTSP/RTMP H.264 broadcasting. This connectivity enables the use of a second display or lecture recording system during virtual meetings, resulting in seamless hybrid meeting experiences for your business.

# **Support Video and Audio with One USB Cable Solution**

Setting up the VC520 Pro3 is simple. Plugging a single USB cable into your computer is all it takes to get ready for a call, which saves time and helps you maintain an uncluttered meeting space. Simplify your setup and reduce installation costs with the VC520 Pro3.

# **Exceptional Audio Quality with** an Extended Speakerphone

The VC520 Pro3 delivers a consistent and well-balanced audio performance. Also, it accommodates either two expansion speakerphones or a full-duplex microphone set. This innovative speakerphone feature makes the VC520 Pro3 the ideal choice for mid-to-large conference













